
## 415 Pebble Step Sof-Tred™ w/Dyna-Shield® Anti-Fatigue/Anti-Slip Matting







manufactured with a tough protective top layer that provides long lasting wear and outperforms the competition in tear resistance and tensile strength. Designed for use in medium duty dry work areas.

**Test Test Description** \*Results Test specimen is subjected to varying compression load levels and Compression Deflection the resulting deflection was measured. The greater the deflection, .961" (40 lbs/sq. inch) the better the anti-fatigue properties. (Inches) A neolite heel assembly with a predetermined load is pulled Coefficient of Friction .79 horizontally with a dynamometer to measure the force ASTM C1028-96 required to cause the assembly to slip. Test specimen is subjected to the rubbing action of two Abrasion Resistance 10.8 Grams (71.2%) abrading wheels under controlled conditions. ASTM D3884-01 (5,000 cycles) Results measured in Weight loss (Grams) 25.9 lbs Test specimen is stretched at a specified rate until breaking Elongation point. The results are measured in % of size increase at 80.1% ASTM D412 (average of 5 specimens) breaking point. This test is designed to measure the force required to initiate Tear Strength tearing. The maximum stress, usually found near the outset of 11.9 **ASTM D1004** tearing, is recorded as the tear resistance in pounds (force)



- Top surface easy to sweep clean
- Overall thickness: 3/8"
- All four sides are beveled to minimize trip hazards
- Stock Sizes: 2' x 3', 2' x 6', 3' x 4', 3' x 5', 3' x 6', 3' x 12'

• Roll Sizes: 2' x 60', 3' x 60', 4' x 60'

Custom sizes available in 2', 3', and 4' widths



Anti-Fatique



Custom Lengths



<sup>\*</sup>All testing of NoTrax® floor matting has been performed by an independent testing laboratory.