


MODEL No: 0462-AD9

ISSUED: 1-87

REVISED: 9-04

## SURFACE MOUNTED PAPER TOWEL DISPENSER AND WASTE RECEPTACLE



### **SPECIFICATION**

Surface Mounted Paper Towel Dispenser and Waste Receptacle shall hold and dispense 475 standard multi-fold or (350) standard C-fold paper towels and shall have a waste capacity of 2 gal. (7.6 liters). Door and cabinet shall be fabricated of alloy 18-8 stainless steel, type 304, 22 gauge; all exposed surfaces shall have N° 4 satin finish and be protected during shipment with a PVC film that shall be easily removable after installation. Door shall be of double-pan construction with fiberboard filler and shall be attached to cabinet at side with a full length 3/16" dia. stainless steel multi-staked piano hinge and shall be held closed with a tumbler lock keyed alike to other ASI washroom equipment. Towel dispensing slot shall have a fully deburred edge for snag-free dispensing and user safety. Waste receptacle shall have hemmed edges and a rolled-edge finger-hole for ease of service removal and maintenance safety. Structural assembly of body and door components shall be of welded construction. Unit shall be supplied with SM collar to convert to surface mounting.

### **INSTALLATION**

Unit is surface mounted to wall using N° 10 self tapping screws (by others) through concealed mounting holes provided. For compliance with ADA Accessibility Guidelines, unit should be installed so that towel dispenser slot is 54" (1372mm) maximum above finished floor (AFF) if clear floor side reach access is provided or 48" (1219mm) maximum AFF if clear floor forward reach access only is provided. SM collar is installed on cabinet prior to mounting on wall following procedure described on SM Collar Data Sheet.

### **OPERATION**

Towels are self-feeding until supply is depleted. Unit may be reloaded with a partial load in-place and will continue to feed properly. Waste container is emptied manually on cycle determined by maintenance needs.